

570W

HORAY

TIER1
BloombergNEF

HS 191R-132 TC Basin N-type Mono-facial Modules



SMBB Half-Cell Technology

More uniform current collection capability, reducing the current heat loss of the internal cells.



Higher Output Power

The output power of 132 half-cells monocrystalline modules is up to 570W.



Low Light Features

Higher performance under low light environment.




Harsh Environmental Adaptability

Strict salt spray and ammonia corrosion test by the third party.



N-type With Very Low LID

N-type solar cell has very low LID naturally which can reduce power degradation.



IEC61215:2021

IEC61730:2023

ISO9001:2015 Quality Management System


ISO14001:2015 Environmental Management System

ISO45001:2018 Occupational Health and Safety Management System

CE: Europe Standard

China Quality Certification Centre

Solar Product Certification



12-year product warranty



30-year linear power output warranty

HEADQUARTER: HORAY SOLAR CO., LTD.

GLOBAL MARKETING AND SERVICE: HORAY SOLAR GMBH


sales@horaysolar.com www.horaysolar.com +86-510 83580688

No.300 Huiming Road, Huishan District, 214177 Wuxi, Jiangsu, P.R. China

info@horaysolar.com www.horaysolar.com

Robert-Bosch-Straße 27-29, 63225 Langen, Germany


MECHANICAL DIAGRAMS



MECHANICAL PARAMETERS

Weight	25.5kg
Dimension	2188×1134×30mm
Cell Orientation	132 (6×22)
Junction Box	IP68, three diodes
Output Cable	4mm²,±300mm (length can be customized)
Connector	MC4 compatible
Glass	3.2mm AR coated heat strengthened glass
Frame	Anodized aluminum alloy frame
Packaging	37pcs per pallet/740pcs per 40'HC

MECHANICAL PARAMETERS



ELECTRICAL CHARACTERISTICS AT STC

Module Type	HS550TC-MHB	HS555TC-MHB	HS560TC-MHB	HS565TC-MHB	HS570TC-MHB
Testing Condition	STC	STC	STC	STC	STC
Maximum Power(Pmax/W)	550	555	560	565	570
Open Circuit Voltage(Voc/V)	47.55	47.76	47.98	48.05	48.41
Short Circuit Current(Isc/A)	14.52	14.59	14.65	14.76	14.78
Maximum Power Voltage(Vmp/V)	40.33	40.52	40.70	40.76	41.07
Maximum Power Current(Imp/A)	13.64	13.70	13.76	13.86	13.88
Module Efficiency(%)	22.2	22.4	22.6	22.8	23.0

* Under Standard Test Conditions (STC) of irradiance of 1000 W/m², spectrum AM 1.5 and cell temperature of 25°C.

ELECTRICAL CHARACTERISTICS AT NMOT

Module Type	HS550TC-MHB	HS555TC-MHB	HS560TC-MHB	HS565TC-MHB	HS570TC-MHB
Testing Condition	NMOT	NMOT	NMOT	NMOT	NMOT
Maximum Power(Pmax/W)	461	465	469	474	478
Open Circuit Voltage(Voc/V)	47.55	47.76	47.98	48.05	48.41
Short Circuit Current(Isc/A)	11.07	11.12	11.17	11.25	11.26
Maximum Power Voltage(Vmp/V)	40.33	40.52	40.70	40.76	41.07
Maximum Power Current(Imp/A)	10.39	10.44	10.48	10.56	10.58

* Under Nominal Module Operating Temperature (NMOT), irradiance of 800 W/m², spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s.

OPERATING PARAMETERS

Operational Temperature	-40°C~+85°C
Power Output Tolerance	0~3%
Maximum System Voltage	1500V
Maximum Series Fuse Rating	30A
Nominal Operating Cell Temperature	45±2°C
Protection Class	Class II
Fire Rating	IEC Class C

*The actual test value may be slightly deviated from the technical parameters due to the difference in test methods.

MECHANICAL LOADING

Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm Hailstone at the speed of 23m/s

TEMPERATURE RATINGS (STC)

Temperature Coefficient of Isc	+0.04%/°C
Temperature Coefficient of Voc	-0.23%/°C
Temperature Coefficient of Pmax	-0.28%/°C



YouTube



FaceBook



Linkedin



WeChat